



XL型星形弹性联轴器的基本参数及主要尺寸

型号	公称扭矩 N.m	许用转速 r/min	轴孔直径 d1、d2mm	轴孔长 度 Lmm	L0 mm	D mm	D1D2 mm	E mm	S mm	转动惯量 Kg.cm ²	重量 Kg
XL0	12.5	19000	6-16	18	50	30	30	13	1.5	0.00005	0.10
XL1	17	19000	6-19	25	66	40	32	16	2	0.00008	0.30
XL2	60	14000	8-24	30	78	55	40	18	2	0.0002	0.61
XL3	160	11800	10-28	35	90	65	48	20	2.5	0.0007	1.00
XL4	325	9500	12-38	45	114	80	66	24	3	0.002	2.08
XL5	450	8000	14-42	50	126	95	75	26	3	0.004	3.21
XL6	525	7100	15-48	56	140	105	85	28	3.5	0.006	4.41
XL7	685	6300	20-55	65	160	120	98	30	4	0.012	6.64
XL8	940	5600	22-65	75	185	135	115	35	4.5	0.025	10.31
XL9	1920	4750	30-75	85	210	160	135	40	5	0.054	16.03
XL10	3600	3750	40-90	100	245	200	160	45	5.5	0.139	27.50
XL11	4950	3350	50-100	110	270	225	180	50	6	0.245	38.50
XL12	7200	3000	60-110	120	295	255	200	50	6.5	0.435	54.00
XL13	10000	2650	60-125	140	340	290	230	60	7	0.85	81.80
XL14	12800	2380	60-140	155	375	320	255	65	7.5	1.4	109.70
XL15	19200	2000	80-160	175	425	370	290	75	9	2.72	162.70
XL16	28000	1800	85-180	195	475	420	325	85	10.5	4.95	230.80